



SPECIFICATIONS

The fitting is delivered with an integrated BALLOFIX® ball valve.

Handle: Metal, BROEN POLYCOAT powder coated with media indication according to EN13792

Spout: Full swivel action

Hose nozzle: Removable metal

Headwork: Ceramic

Opening/closing function: 180° (wrist action lever: 90°)

Temperature range: 0-90°C

Max. working pressure: 10 bar / 147 psi

Test pressure: 1 x working pressure

Weight: 1.4 kg

MATERIALS WITH MEDIA CONTACT

Metals: Brass

Plastics: POM, PTFE, SPX (hose)

Sealing: EPDM

Lubricant: Silicone based

Ceramics: Al₂O₃ 96%

ORDERING INFORMATION

For standard configuration please refer to the item numbers below.

Other options:

- aerator
- fixed hose nozzle
- integrated non-return valve
- fixed spout
- alternative hose inlet connection / without a hose
- other inlet options (type, length)
- national approvals
- WPH (Water Potable Hot)
- WNH (Water Non-Potable Hot)

With wrist action lever



Model: Metal handle

Media	S = 150mm	S = 200mm	S = 250mm	S = 300mm
Potable water, cold	2534 001 1001-52B	2534 002 1001-52B	2534 017 1001-52B	2534 016 1001-52B
Non-potable water, cold	2534 001 1007-52B	2534 002 1007-52B	2534 017 1007-52B	2534 016 1007-52B

Model: Wrist action lever



Media	S = 150mm	S = 200mm	S = 250mm	S = 300mm
Potable water, cold	2534 015 1001-52B	2534 018 1001-52B	2534 050 1001-52B	2534 051 1001-52B
Non-potable water, cold	2534 015 1007-52B	2534 018 1007-52B	2534 050 1007-52B	2534 051 1007-52B

For further information and mounting instructions please refer to www.BROEN.com or contact your local BROEN LAB representative.