

TEMPOMIX shower kit

Ref. 790912

Single control time flow







DESCRIPTION

TEMPOMIX shower kit - Ref. 790912

Recessed time flow shower kit:
 Standard recessing housing. Recessing depth can be adjusted.
 Chrome-plated wall plate Ø 195mm. Recessing depth can be adjusted from 28 - 43mm.
 TEMPOMIX 3/4" single control mixer.
 Ligature-resistant collar.
 Temperature control and operation via the push-button.
 Maximum temperature limiter (can be adjusted by the installer).
 Time flow ~30 seconds, soft-touch operation.
 Flow rate 6 lpm at 3 bar.
 Chrome-plated, tamperproof TONIC JET shower head with scale-resistant nozzle and automatic flow rate regulation.
 M1/2" connectors for copper tubes Ø 14mm.
 Integrated non-return valves and filters.
 Chrome-plated metal control.
 10-year warranty.




This model does not have a waterproof recessing box. The installer must ensure that the recessing area is waterproof and any leaks or condensates can drain away (see installation guide).

ADVANTAGES

-  Water savings up to 80%
-  Wall recessed installation
-  Time flow system tested to over 500000 operations
-  Soft-touch operation

TECHNICAL FEATURES

TEMPOMIX shower kit - Ref. 790912

Connector	1/2"
Technology	Time flow
Flow rate	6 lpm
Standards and certifications	  
Warranty	