

## TEMPOMIX 3 shower mixer

Ref. 794BOX1-794218

Time flow single control, top inlet



### DESCRIPTION

**TEMPOMIX 3 shower mixer - Ref. 794BOX1-794218**




Recessed time flow shower mixer with soft-touch operation:  
Tamperproof chrome-plated metal wall plate 160 x 160mm.

Waterproof recessing housing:

- Collar with waterproof seal.
  - Hydraulic connection from the exterior and maintenance from the front.
  - Top inlet.
  - Adjusts to all types of installation (rails, solid walls, panels).
  - Compatible with wall finishes 10 - 120mm (while maintaining the minimum recessing depth of 93mm).
  - Suitable for standard pipe supply or "pipe in pipe".
  - Stopcocks and flow rate adjustment, filters, non-return valves and cartridge are integrated and can be accessed from the front.
  - TEMPOMIX 3 single control mixer 1/2".
  - Supplied in 2 kits: secure system flush without sensitive elements.
- Temperature control and operation via the push-button.  
Maximum temperature limiter (can be adjusted by installer).  
Time flow ~30 seconds, can be adjusted.  
Soft-touch operation.  
Flow rate 9 lpm at 3 bar.  
Suitable for people with reduced mobility.  
10-year warranty.

### TECHNICAL CHARACTERISTICS

**TEMPOMIX 3 shower mixer - Ref. 794BOX1-794218**

Connector	1/2"
Technology	Time flow
Height	160mm
Depth	93-190mm
Width	160mm
Flow rate	9 lpm
Norms	 
Warranty	

### ADVANTAGES



Soft-touch operation



Recessed installation, concealed fixings



Adjustable, modular waterproof housing



Time flow system tested to over 500,000 operations

