

TEMPOMIX 3 shower kit

Ref. 794BOX1-794219

Time flow single control, top inlet



DESCRIPTION

TEMPOMIX 3 shower kit - Ref. 794BOX1-794219


Recessed time flow shower mixer with soft-touch operation:
 Tamperproof chrome-plated metal wall plate 160 x 160mm.
 Waterproof recessing housing:
 - Collar with waterproof seal.
 - Hydraulic connection from the exterior and maintenance from the front.
 - Top inlet.
 - Adjusts to all types of installation (rails, solid walls, panels).
 - Compatible with wall finishes 10 - 120mm (while maintaining the minimum recessing depth of 93mm).
 - Suitable for standard pipe supply or "pipe in pipe".
 - Stopcocks and flow rate adjustment, filters, non-return valves and cartridge are integrated and can be accessed from the front.
 - TEMPOMIX 3 single control mixer F1/2".
 - Supplied in 2 kits: secure system flush without sensitive elements.
 Temperature control and operation via the push-button.
 Maximum temperature limiter (can be adjusted by installer).
 Time flow ~30 seconds, can be adjusted.
 Soft-touch operation.
 Flow rate 6 lpm at 3 bar.
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
 10-year warranty.

ADVANTAGES

-  80% water savings
-  Soft-touch operation
-  Recessed installation, concealed fixings
-  Adjustable, modular waterproof housing

TECHNICAL FEATURES

TEMPOMIX 3 shower kit - Ref. 794BOX1-794219

Connector	1/2"
Technology	Time flow
Height	160mm
Depth	93-190mm
Width	160mm
Flow rate	6 lpm
Standards and certifications	
Warranty	