TEMPOMATIC shower kit

Ref. 452159

Electronic



DESCRIPTION

TEMPOMATIC shower kit - Ref. 452159

Cross wall electronic shower kit:

TEMPOMATIC electronic valve for mixed water supply.

For walls ≤ 155 mm.

Power supply by electronic unit with solenoid valve 1/2".

230/12V transformer.

2 operation modes:

- Automatic activation via presence detection.
- Voluntary ON/OFF activation by passing the hand in front of sensor $\sim\!10$ cm.

Duty flush (~60 seconds every 24 hours after the last use).

Adjustable time flow from 30 to 60 seconds.

Flow rate set at 6 lpm at 3 bar.

Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.

Chrome-plated solid brass.

Wall plate flush to the wall.

Threaded rods can be cut-to-size.

10-year warranty.





230/12V



Total hygiene: no manual contact



Anti-bacterial duty flush




2 operation modes

TECHNICAL FEATURES

TEMPOMATIC shower kit - Ref. 452159

Supply	230/12V mains supply
Connector	1/2"
Technology	Electronic
Length	155mm
Flow rate	6 lpm
Standards and certifications	⊜ (€
Warranty	MANAGE TO THE PARTY OF THE PART





© DELABIE