

SECURITHERM shower panel

Ref. 792310

Thermostatic time flow







DESCRIPTION

SECURITHERM shower panel - Ref. 792310

Thermostatic time flow shower panel:
 Anodised aluminium shower panel for wall-mounted, exposed installation.
 Concealed inlet via flexibles M1/2".
 SECURITHERM thermostatic mixer.
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
 Anti-scalding safety: automatic shut-off if cold or hot water supply fails.
 Thermal shocks are possible.
 Soft-touch operation.
 Time flow ~30 seconds.
 Flow rate set at 6 lpm at 3 bar.
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
 Concealed fixings.
 Filters and non-return valves.
 10-year warranty.

ADVANTAGES

-  Thermostatic control
-  Instant shut-off if cold water fails
-  Water savings up to 80%
-  Aluminium panel, brass controls

TECHNICAL FEATURES

SECURITHERM shower panel - Ref. 792310

Connector	M1/2"
Technology	Time flow
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Standards and certifications	   
Warranty	

