

## SECURITHERM shower panel

Ref. 792320

Thermostatic time flow dual control




### DESCRIPTION

#### SECURITHERM shower panel - Ref. 792320

SECURITHERM dual control thermostatic time flow shower panel:  
 Anodised aluminium shower panel for wall-mounted, exposed installation.  
 With top inlet via in-line stopcocks, M1/2".  
 SECURITHERM thermostatic mixer.  
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
 Anti-scalding safety: automatic shut-off if cold or hot water supply fails.  
 Thermal shocks are possible.  
 Time flow valve ~30 seconds with soft-touch operation.  
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.  
 Handset with removable flexible via push-fit rapid STOP connector and wall support supplied.  
 Concealed fixings.  
 Filters and non-return valves.  
 10-year warranty.





### TECHNICAL FEATURES

#### SECURITHERM shower panel - Ref. 792320

Connector	M1/2"
Technology	Time flow
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	thermostatic
Finish	Aluminium
Standards and certifications	 
Warranty	



### ADVANTAGES

-  Thermostatic temperature regulation
-  Immediate shut-off in the event of cold water failure
-  80% water savings
-  Aluminium body, brass controls

