

SECURITHERM shower panel

Ref. 792340

Dual control thermostatic mixer




DESCRIPTION

SECURITHERM shower panel - Ref. 792340

Dual control thermostatic shower panel:
 Anodised aluminium shower panel for wall-mounted, exposed installation.
 Top inlets via in-line stopcocks M1/2".
 SECURITHERM thermostatic mixer.
 Adjustable temperature control from cold water up to 38°C; with 1st limiter set at 38°C and 2nd limiter set at 41°C.
 Anti-scalding safety: automatic shut-off if cold or hot water supply fails.
 Time flow valve ~30 seconds with soft-touch operation to control the ROUND shower head.
 Non-time flow 1/4-turn valve controls the hand set.
 Thermal shocks are possible.
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.
 Handset with removable flexible via rapid push-fit STOP connector and wall support supplied.
 Concealed fixings.
 Filters and non-return valves.
 10-year warranty.





TECHNICAL FEATURES

SECURITHERM shower panel - Ref. 792340

Connector	M1/2"
Technology	Dual control
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	thermostatic
Finish	Aluminium
Standards and certifications	 
Warranty	



ADVANTAGES

-  Thermostatic temperature regulation
-  Immediate shut-off if cold water fails
-  80% water savings
-  Aluminium casing, brass mixer

