

SECURITHERM shower panel

Ref. 792344

Thermostatic mechanical dual control

DESCRIPTION

SECURITHERM shower panel - Ref. 792344

Dual control thermostatic shower panel with handset.
Large model stainless steel shower panel for wall-mounted, exposed installation.

Top inlet via in-line stopcocks M1/2".

SECURITHERM thermostatic mixer.

Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.

Anti-scalding safety: automatic shut-off if cold or hold water supply fails.

Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation set at 6 lpm at 3 bar.

Handset with removable flexible via rapid push-fit STOP connector, wall support supplied.

Non-time flow valves control the ROUND shower head and the handset.

Thermal shocks are possible.



Concealed fixings.

Filters and non-return valves.

10-year warranty.





TECHNICAL FEATURES

SECURITHERM shower panel - Ref. 792344

Connector	M1/2"
Technology	Non-time flow
Height	1220mm
Depth	100mm
Width	250mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Stainless steel
Standards and certifications	
Warranty	



ADVANTAGES

-  Thermostatic control
-  Instant shut-off if cold water fails
-  Fixed shower head or handset
-  Aluminium panel, brass controls

