SECURITHERM shower panel

Ref. 792410

Electronic battery-operated thermostatic



ADVANTAGES



Total hygiene: operate without manual contact



Automatic flush anti-bacterial proliferation



Thermostatic control



Instant shut-off if cold water supply fails

DESCRIPTION

SECURITHERM shower panel - Ref. 792410

Electronic thermostatic shower panel:

Anodised aluminium shower panel for wall-mounted, exposed installation.

With concealed inlet via flexibles, M1/2".

SECURITHERM thermostatic mixer.

Adjustable temperature control from cold water up to 38 $^{\circ}\text{C}$ with 1st limiter set at 38 $^{\circ}\text{C}$ and 2nd limiter set at 41 $^{\circ}\text{C}$.

Anti-scalding safety: automatic shut-off if cold or hot water supply fails.

Thermal shocks are possible.

Battery-operated with 223 6V Lithium battery.

Infrared presence detection. Shower starts when hand is 4cmfrom the sensor.

Shuts off on demand or automatically after ~60 seconds.

Duty flush (~60 seconds every 24 hours after the last use).

Flow rate set at 6 lpm at 3 bar.

Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.

Concealed fixings.


Filters and non-return valves.

10-year warranty.

TECHNICAL FEATURES

SECURITHERM shower panel - Ref. 792410

Supply	6V battery
Connector	M1/2"
Technology	Electronic
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Standards and certifications	
Warranty	



© DELABIE https://www.delabie.com