

## SECURITHERM shower panel

Ref. 792514

Electronic mains supply thermostatic







### DESCRIPTION

#### SECURITHERM shower panel - Ref. 792514



Electronic thermostatic shower panel:  
 Large stainless steel panel for wall-mounted, exposed installation.  
 Concealed inlet via flexibles M1/2".  
 SECURITHERM thermostatic mixer.  
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
 Anti-scalding safety: automatic shut-off if cold or hot water supply fails.  
 Thermal shocks are possible.  
 Mains supply 230/6V.  
 Shower starts when electronic push-button is pressed.  
 Shuts off voluntarily or automatically after ~60 seconds.  
 Duty flush (~60 seconds every 24 hours after the last use).  
 Flow rate 6 lpm at 3 bar.  
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.  
 Integrated soap dish.  
 Filters and non-return valves.  
 Stopcocks M1/2".  
 Concealed fixings.  
 10-year warranty.

### ADVANTAGES

-  80% water savings
-  Duty flush limits proliferation of bacteria
-  Thermostatic temperature regulation
-  Instant shut-off if cold water fails

### TECHNICAL FEATURES

#### SECURITHERM shower panel - Ref. 792514

Supply	230/6V mains supply
Connector	M1/2"
Technology	Electronic
Height	1220mm
Depth	100mm
Width	250mm
Flow rate	6 lpm
Temperature limiter	thermostatic
Finish	Stainless steel
Standards and certifications	 
Warranty	