TEMPOMIX 3 shower kit

Ref. 794450

Time flow single control



ADVANTAGES



80% water savings



Soft-touch operation



Time flow system tested to over 500,000 operations

DESCRIPTION

TEMPOMIX 3 shower kit - Ref. 794450

Exposed time flow shower kit:

TEMPOMIX 3 single control mixer 3/4", top outlet.

For wall-mounted, exposed installation.

Temperature control and operation via the push-button.

Maximum temperature limiter (can be adjusted by the installer).

Soft-touch operation.

Time flow pre-set at ~30 seconds, can be adjusted from 20 - 30 seconds.

Flow rate 6 lpm at 3 bar.

Chrome-plated, tamperproof, scale-resistant TONIC JET shower head with automatic flow rate regulation.

Chrome-plated solid brass.

Integrated filters and non-return valves.

Chrome-plated metal push-button.

Shower column Ø 16mm with reinforced collar (fixing plate and screws included).

M1/2" offset connectors for 130 - 170mm centres.

10-year warranty.

TECHNICAL FEATURES

TEMPOMIX 3 shower kit - Ref. 794450

Connector	M1/2"
Technology	Time flow
Height	1010mm
Width	150mm
Flow rate	6 lpm
Standards and certifications	1
Warranty	



© DELABIE https://www.delabie.com