

SECURITHERM Securitouch thermostatic shower mixer

Ref. H9741

Dual control mixer with thermal insulation







DESCRIPTION

SECURITHERM Securitouch thermostatic shower mixer - Ref. H9741

SECURITHERM dual control thermostatic shower mixer with:









- Anti-scalding failsafe: hot water shuts off immediately if cold water supply fails (and vice versa).
 - Securitouch thermal insulation to prevent burns.
 - Scale-resistant thermostatic cartridge for temperature adjustment.
 - 1/4-turn ceramic head for flow rate adjustment.
 - Temperature control: 25 - 41 °C.
 - Double temperature limiter: first limiter set at 38°C can be overridden, second limiter set at 41 °C.
 - Thermal shocks are easy to undertake without removing the control knob or shutting off the cold water supply.
 - Flow rate regulated at 9 lpm.
 - Chrome-plated brass body and ERGO controls.
 - M1/2" shower outlet.
 - M3/4" inlets with integrated filters and non-return valves.
- Mixer supplied with offset M1/2" M3/4" STOP/PURGE connectors, suitable for hospitals.
10-year warranty.

ADVANTAGES

-  SECURITHERM: Optimum anti-scalding safety
-  Double temperature limiter
-  Securitouch thermal insulation prevents burns
-  Thermostatic: complete temperature stability

TECHNICAL FEATURES

SECURITHERM Securitouch thermostatic shower mixer - Ref. H9741

| | |
|------------------------------|---|
| Connector | M1/2" |
| Technology | SECURITHERM dual control thermostatic, Securitouch |
| Depth | 95mm |
| Length | 286mm |
| Flow rate | 9 lpm |
| Temperature limiter | 41 °C |
| Finish | Chrome-plated brass |
| Standards and certifications |        |
| Warranty |  |

