

TEMPOMATIC tap with BIOCLIP spout

Ref. 20804T2

Electronic wall-mounted tap with mains supply



DESCRIPTION

TEMPOMATIC tap with BIOCLIP spout - Ref. 20804T2

Wall-mounted electronic tap with BIOCLIP removable spout for mounting on panels.

Independent IP65 electronic control unit.

230/12V mains supply with transformer

Tap supplied with 2 removable BIOCLIP stainless steel spouts L. 129mm.

Base and spout with smooth interiors (reduces bacterial development).

Adjustable duty flush (pre-set at ~60 seconds every 24 hours after last use).

Flow rate limited to 4 lpm at 3 bar.

Separate sensor for mounting on panels.

M3/8" solenoid valve with integrated filter.

Shock-resistant infrared presence detection sensor.

Ø 60mm chrome-plated brass base.

Anti-blocking security.

Recommended installation height: 110 - 200mm above the basin surface.

Suitable for people with reduced mobility.

10-year warranty.

Two shut-off options:







- standard mode: timed flow with automatic shut-off.

- ON/OFF mode: user shuts off flow voluntarily or automatic shut-off after 30 minutes of flow.

Thermal shocks are possible.

TECHNICAL CHARACTERISTICS

TEMPOMATIC tap with BIOCLIP spout - Ref. 20804T2

Connector	3/8"
Technology	Electronic
Depth	190mm
Length	129mm
Spout length	188mm
Flow rate	4 lpm
Finish	Chrome-plated brass
Norms	    
Warranty	

ADVANTAGES



Automatic duty flush limits bacterial development



Hygiene: spout can be removed and descaled inside



Hygiene: smooth interior reduces bacteria



Infrared detection with no manual contact

