

Sequential mechanical basin mixer

Ref. 2436S

Sequential mechanical mixer with swivelling spout L. 200mm







DESCRIPTION

Sequential mechanical basin mixer - Ref. 2436S





Wall-mounted 90° sequential basin mixer.
 Open and closing on cold water.
 Flat swivelling under spout L. 200mm with hygienic flow straightenersuitable for fitting a BIOFIL terminal filter.
 Securitouch thermal insulation prevents burns.
 Ø 35mm ceramic cartridge with pre-set maximum temperature limiter.
 Body and spout with smooth interiors and low water volume(reduces bacterial development).
 Flow rate regulated at 5 lpm.
 Chrome-plated brass body.
 Non-manual contact operation with Hygiene control lever L. 200mm.
 Supplied with two standard connectors M1/2" M3/4".
 10-year warranty.

TECHNICAL CHARACTERISTICS

Sequential mechanical basin mixer - Ref. 2436S

Connector	M1/2"
Technology	Securitouch
Spout length	200mm
Flow rate	5 lpm
Finish	Chrome-plated brass
Norms	  
Warranty	

ADVANTAGES

-  Sequential opening and closing on cold water
-  Body/spout with smooth interiors, reduces bacteria
-  Securitouch anti-scalding thermal insulation
-  Pre-set maximum temperature limiter

