

Free-standing eye wash station

Ref. 9201

Manual and pedal control



DESCRIPTION

Free-standing eye wash station - Ref. 9201


Free-standing eye wash station with manual and pedal control includes:
 Frost-free system as standard.
 304 stainless steel basin Ø 250mm, green powder-coated finish.
 2 eye wash spray heads fitted with protective caps in shock-resistant green ABS; will eject automatically when activated.
 1/4-turn, nickel-plated brass valves open and close quickly.
 Water flow is activated by hand or foot control. The eye wash will continue to operate when the hand or foot control is released. The flow stops when the hand control is pulled towards the user or the foot pedal is raised.
 Flow rate 20 lpm at 3 bar.
 Aerators with stainless steel double filters.
 Water supply F1".
 Pipework made from galvanised steel, grey powder-coated finish.
 Hand and foot controls in green powder-coated galvanised steel.
 Fixed to the floor by a triangular brass plate (screws not included.)
 Supplied with identification sign for first aid equipment: "Eye Wash".
 10-year warranty.

ADVANTAGES

-  Frost-free system provided as standard
-  Gentle spray, quick and easy to activate
-  Maintenance without removing the equipment
-  Rapid flow rates for decontamination

TECHNICAL FEATURES

Free-standing eye wash station - Ref. 9201

Height	1050mm
Depth	500mm
Flow rate	20 lpm
Finish	Epoxy
Standards and certifications	
Warranty	