

## SECURITHERM EP BIOSAFE pressure- balancing basin mixer

Ref. 26216EP

Mixer with no spout H. 95mm L. 110mm

### DESCRIPTION

#### SECURITHERM EP BIOSAFE pressure-balancing basin mixer - Ref. 26216EP

SECURITHERM basin mixer H. 95mm L. 110mm with pressure balancing.

No spout: BIOSAFE hygienic outlet integrated into the body.

Anti-scalding safety: HW flow rate is reduced if CW supply fails.

Securitouch thermal insulation prevents burns.

Ø 35mm ceramic cartridge with pressure balancing.

Pre-set maximum temperature limiter.

Thermal shocks are possible without removing the control lever or shutting off the cold water supply.

Body with smooth interior and very low water volume (reduces bacterial development).

Flow rate limited to 4 lpm at 3 bar.

Solid control lever.

Mixer without pop-up waste.



Reinforced fixing via two stainless steel rods.

Supplied with copper tails and Ø 15mm stopcocks.

10-year warranty.

### TECHNICAL FEATURES

#### SECURITHERM EP BIOSAFE pressure-balancing basin mixer - Ref. 26216EP

|                              |   |
|------------------------------|---|
| Connector                    | M1/2"   |
| Technology                   | SECURITHERM EP BIOSAFE  |
| Height                       | 180mm   |
| Length                       | 220mm   |
| Drop height                  | 95mm  |
| Spout length                 | 110mm   |
| Flow rate                    | 4 lpm   |
| Temperature limiter          | 41 °C   |
| Finish                       | Chrome-plated brass   |
| Standards and certifications |  |
| Warranty                     |  |



### ADVANTAGES



HW flow rate reduced if CW fails



Body with very low water volume



Thermal shocks are possible without removing lever



No spout

