## **BLACK BINOPTIC electronic** tap

Ref. 379ENCB

Mains supply, L. 200mm



## **DESCRIPTION**

**BLACK BINOPTIC electronic tap - Ref. 379ENCB** 

Recessed electronic basin tap:

Independent IP65 electronic control unit.

230/12V mains supply with transformer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use). Active, infrared presence detection, sensor at the end of the spout optimises detection.

Filter and solenoid valve M3/8".

Chrome-plated brass body.

Matte black chrome finish.

Recessed installation.

Anti-blocking safety.

Spout with smooth interior and low volume of water (limits bacterial niches). Suitable for people with reduced mobility.

10-year warranty.

## **TECHNICAL CHARACTERISTICS**

**BLACK BINOPTIC electronic tap - Ref. 379ENCB** 

Supply	Mains supply 230/12V
Connector	M3/8"
Technology	Electronic
Spout length	200mm
Flow rate	3 lpm
Finish	Matte black chrome
Norms	ACS W CE
Warranty	

## **ADVANTAGES**



Total hygiene: no manual contact




90% water savings



100% matte black chrome finish



Anti-bacterial proliferation duty flush



© DELABIE https://www.delabie.com