

TEMPOMATIC 4 electronic tap

Ref. 440006

Integrated batteries, stopcock



DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 440006

Deck-mounted electronic basin tap:
 Battery-operated with integrated 123 6V Lithium batteries.
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm.
 Scale-resistant flow straightener.
 Duty flush (~60 seconds every 24 hours after last use).
 Active, infrared presence detection, sensor at the end of the spout optimises detection.
 Chrome-plated metal body.
 Cap fixed in place by 2 concealed screws.
 PEX flexible with stopcock F3/8" and filter.
 Fixing reinforced by two stainless steel rods.
 Anti-blocking security.
 Suitable for people with reduced mobility.
 10-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref. 440006

Supply	6V batteries
Connector	F3/8"
Technology	Electronic
Drop height	75mm
Spout length	110mm
Flow rate	3 lpm
Norms	
Warranty	

ADVANTAGES



Total hygiene: no manual contact



90% water savings



Batteries integrated into the body of the tap



Anti-bacterial proliferation duty flush

