

BINOPTIC MIX electronic mixer

Ref. 478MCHLH

Battery-operated







DESCRIPTION

BINOPTIC MIX electronic mixer - Ref. 478MCHLH


Deck-mounted electronic basin mixer:
 Independent IP65 electronic control unit.
 123 6V Lithium battery-operated.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm.
 Scale-resistant flow straightener.
 Adjustable duty flush (pre-set flush ~60 seconds every 24hr after last use).
 Active, infrared presence detection, sensor at the end of the spout optimises detection.
 Chrome-plated brass body.
 PEX flexibles with filters and solenoid valves M3/8".
 Fixing reinforced by 2 stainless steel rods.
 Anti-blocking safety.
 Spout with smooth interior and low volume of water (reduces niches where bacteria can develop).
 Side temperature control with long lever control and adjustable maximum temperature limiter.
 Suitable for people with reduced mobility.
 10-year warranty.

ADVANTAGES

-  Independent IP65 electronic control unit
-  90% water savings
-  Total hygiene: no manual contact
-  Anti-bacterial proliferation duty flush

TECHNICAL FEATURES

BINOPTIC MIX electronic mixer - Ref. 478MCHLH

Supply	6V battery
Connector	M3/8"
Technology	Electronic
Drop height	110mm
Spout length	135mm
Flow rate	3 lpm
Standards and certifications	
Warranty	