## TEMPOMATIC MIX 4 electronic mixer

Ref. 490001

Plug-in mains supply, stopcocks



## **DESCRIPTION**

TEMPOMATIC MIX 4 electronic mixer - Ref. 490001

Deck-mounted electronic basin mixer:

230/6V plug-in mains supply.

Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm.

Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after the last use).

Active infrared presence detection sensor at the end of the spout optimises detection.

Chrome-plated solid brass body.

Cap fixed in place by 2 concealed screws.

PEX flexibles F3/8" with stopcocks, filters and non-return valves.

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

 ${\bf Side\ temperature\ control\ lever\ with\ adjustable\ maximum\ temperature\ limiter.}$ 

10-year warranty.

## **ADVANTAGES**



Total hygiene: no manual contact



90% water savings



Plug-in mains supply




Anti-bacterial proliferation duty flush

## **TECHNICAL CHARACTERISTICS**

TEMPOMATIC MIX 4 electronic mixer - Ref. 490001

| Supply       | 230/6V plug-in mains supply |
|--------------|-----------------------------|
| Connector    | F3/8"                       |
| Technology   | Electronic                  |
| Drop height  | 75mm                        |
| Spout length | 110mm                       |
| Flow rate    | 3 lpm                       |
| Norms        | (€ ⊜ ⊚                      |
| Warranty     | 10                          |



© DELABIE https://www.delabie.com