

TEMPOMATIC MIX 3 electronic mixer

Ref. 492006LH

Integrated battery, stopcocks







DESCRIPTION

TEMPOMATIC MIX 3 electronic mixer - Ref. 492006LH



Deck-mounted electronic basin mixer:
 Battery-operated with integrated 223 6V Lithium batteries.
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm.
 Scale-resistant flow straightener.
 Duty flush (~60 seconds every 24 hours after last use).
 Active, infrared presence detection, sensor at the end of the spout optimises detection.
 Chrome-plated solid brass body.
 Cap fixed in place by 2 concealed screws, with pictogram to easily identify sensor.
 PEX flexibles with stopcocks, filters and non-return valves.
 Fixing reinforced by 2 stainless steel rods.
 Anti-blocking security.
 Side temperature control with long lever and adjustable maximum temperature limiter.
 Suitable for people with reduced mobility.
 10-year warranty.

ADVANTAGES

-  Battery integrated into the body of the tap
-  90% water savings
-  Total hygiene: no manual contact
-  Anti-bacterial proliferation duty flush

TECHNICAL FEATURES

TEMPOMATIC MIX 3 electronic mixer - Ref. 492006LH

Supply	6V battery
Connector	F3/8"
Technology	Electronic
Drop height	100mm
Spout length	120mm
Flow rate	3 lpm
Standards and certifications	 
Warranty	