TEMPOMATIC MIX 3 electronic mixer

Ref. 492106

Integrated battery



DESCRIPTION

TEMPOMATIC MIX 3 electronic mixer - Ref. 492106

Deck-mounted electronic basin mixer:

Battery-operated with integrated 223 6V Lithium batteries.

Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm.

Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after last use).

Active, infrared presence detection, sensor at the end of the spout optimises detection.

Chrome-plated solid brass body.

Cap fixed in place by 2 concealed screws, with pictogram to easily identify sensor.

PEX flexibles F3/8" with filters and non-return valves.

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Side temperature control with adjustable maximum temperature limiter.

Suitable for people with reduced mobility.

10-year warranty.

ADVANTAGES



Battery integrated into the body of the tap



90% water savings



Total hygiene: no manual contact




Anti-bacterial proliferation duty flush

TECHNICAL FEATURES

TEMPOMATIC MIX 3 electronic mixer - Ref. 492106

Supply	6V battery
Connector	F3/8"
Technology	Electronic
Drop height	100mm
Spout length	120mm
Flow rate	3 lpm
Standards and certifications	
Warranty	



© DELABIE https://www.delabie.com