

TEMPOMATIC MIX 2 electronic mixer

Ref. 494006LH

Battery-operated







DESCRIPTION

TEMPOMATIC MIX 2 electronic mixer - Ref. 494006LH




Deck-mounted electronic basin mixer:
 Independent IP65 electronic control unit.
 123 6V Lithium battery-operated.
 Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm.
 Scale-resistant flow straightener.
 Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
 Shockproof infrared presence detection sensor.
 Chrome-plated solid brass body.
 PEX flexibles with filters and reduced-stagnation solenoid valves M3/8".
 Fixing reinforced by 2 stainless steel rods.
 Anti-blocking safety.
 Side temperature control with long lever and adjustable maximum temperature limiter .
 Solenoid valves upstream of the mixing chamber.
 Suitable for people with reduced mobility.
 10-year warranty.

ADVANTAGES

-  Independent IP65 electronic control unit
-  85% water savings
-  Total hygiene: no manual contact
-  Anti-bacterial proliferation duty flush

TECHNICAL FEATURES

TEMPOMATIC MIX 2 electronic mixer - Ref. 494006LH

Supply	6V battery
Connector	M3/8"
Technology	Electronic
Drop height	125mm
Spout length	145mm
Flow rate	3 lpm
Standards and certifications	  
Warranty	