

TEMPOMATIC dual control plate for WCs

Ref. 464006

Recessed dual control electronic battery-operated valve - For WCs



DESCRIPTION

TEMPOMATIC dual control plate for WCs - Ref. 464006

TEMPOMATIC recessed, dual control, electronic valve for direct flush, kit 2/2: Flush system without cistern: directly connected to pipework.

Battery-operated with CR123 6V Lithium batteries.

Satin finish stainless steel wall plate 186 x 186mm and chrome-plated metal button, with integrated electronics.

TEMPOMATIC F $\frac{3}{4}$ " flush valve is compatible with sea water, rain water and grey water.

Shock-resistant infrared presence detection sensor.

Detection delay is 10 seconds.

Voluntary activation (anti-blocking push-button) or automatically without contact when the user leaves.

Independent push-button: the flush will activate even if the power supply fails.

"Intelligent" automatic rinsing: flush volume adapts according to use - 3L "short" usage, 6L "long" usage - (can be adjusted to 2L/4L or 5L/9L).

3 programmes (rinsing volume can be set according to type of WC pan).

Hygienic duty flush every 24 hours (can be adjusted to 12 hours or OFF) after the last use.

Base flow rate: 1L/sec at 1 bar dynamic pressure.



Suitable for rimless WC pans without flow rate regulation and suitable for people with reduced mobility.

10-year warranty.

Order with frame system references 564060DE or 564065DE, or with recessed housing 464PBOX.

TECHNICAL CHARACTERISTICS

TEMPOMATIC dual control plate for WCs - Ref. 464006

Supply	6V batteries
Connector	F $\frac{3}{4}$ "
Technology	Electronic and time flow
Length	186mm
Width	186mm
Finish	Satin stainless steel
Norms	
Warranty	

ADVANTAGES



Total hygiene: no manual contact



Direct flush: no water stagnation



Voluntary or automatic activation



123 Lithium 6V batteries

