

DUO OUTDOOR SHOWER

Duo Outdoor Shower is made from glass peened stainless steel. The shower is particularly suited for private gardens as well as camping sites, outdoor swimming pools, sea fronts, pool areas etc. The shower is supplied complete with well.

The shower is fitted with a self-emptying 3-way sliding valve, ensuring that the tap remains frost-proof, even at hard freezing temperatures. The seals can be replaced without digging up the well. Unscrew the spindle housing from the top of the pipe stand, then pull up the spindle and replace the O-rings.

Is the product to be placed in an area with a high environmental impact, including sea fog, it is recommended to choose a special design i.e. an electro polished surface.

PRODUCT

Designation: ½" frost-proof water tap for outdoor installation
Tapping: ½" nipple pipe thread
Connection: ¾" nipple pipe thread

INSTALLATION DIMENSIONS

Shower height: 1,950 mm
Shower depth: 220 mm
Pipe stand height: 2,166.50 mm
Height of handle: 795 mm

PRODUCT DIMENSIONS

Overall height incl. well: 3,065 mm
Overall width: 166 mm
Well: D160 x 900 mm

SHIPPING

Dimensions, H-W-D: 3120 x 200 x 400 mm
Weight: 13 kg complete with well

VALVE

FROSTLINE® self-emptying sliding valve
Capacity: 37-45 l/min. at 2-4 bar
O-rings: 8 x 3 mm NBR – shore 70



VA approval No.:ETA – VA 1.51/19066

MODELS

F180	74.34.80.634	Duo Outdoor Shower
F180-1	74.34.85.634	Duo Outdoor Shower w/automatic closing

OPTIONAL

F510	74.34.80.926	Duo Well Ring D60
------	--------------	-------------------

OPERATION OF THE VALVE

The shower is provided with a 3-way self-emptying sliding valve. When the shower is not in use, the valve and riser pipe are emptied of water that might otherwise freeze. The shower and thus the valve and riser pipe are frost-proof as long as the water supply line for it does not freeze.



Duo Outdoor Shower

09.2008