

## WALL – OUTDOOR WALL-MOUNTED WATER TAP

Exclusive outdoor designer tap made from glass peened stainless steel, for wall mounting. This water tap is specially designed for the quality-conscious house and cottage owner, but is also suitable for schools and public buildings where design, functionality and robustness must become one.

Is the product to be placed in an area with a high environmental impact, including sea fog, it is recommended to choose a special design i.e. an electro polished surface.

### PRODUCT

Designation: Outdoor water tap for wall mounting  
 Tapping: ½" nipple pipe thread  
 Connection pressure: 2-6 bar

### INSTALLATION DIMENSIONS

Distance to wall: 40-80 mm  
 Wall clamping: 300-550 mm (shorten to length)  
 150-350 mm (shorten to length)  
 Connection: D15mm copper pipes and ½" pipe thread

### PRODUCT DIMENSIONS

Overall length: 675 mm / 375 mm  
 Overall width: 30 x 70 mm

### SHIPPING

Dimensions, H-W-D: 750 x 100 x 50 mm  
 Weight: 1,6 kg

### VALVE


Ceramic valve with build-in check valve

### O-rings:

8 x 3mm NBR – 70 sh



Wall and Ellipse Hose Bracket



VA approval No.: ETA – VA 1.41/19463

### MODELS

F740	74.34.58.154	Wall water tap 300-550mm
F760	74.34.58.134	Wall water tap 150-350mm

### OPTIONAL

F530	74.34.89.916	Quick coupling - stainless steel
F900	74.34.89.104	Ellipse Hose Bracket, wall-mounted
F921	74.34.89.004	½" 300 mm extension hose w/fittings
F923	74.34.89.014	½" 3,000 mm garden hose with fittings
F926	74.34.89.024	½" 6,000 mm garden hose with fittings
F929	74.34.89.034	½" 9,000 mm garden hose with fittings
F926		½" 600mm garden hose with fittings



The extension hose makes it easier to fill watering cans or buckets.

# FROSTLINE®



WALL WATER TAP