

### Slop closets

Slop closets are used for flushing disposing solid and fluid waste into the drain. For example kidney dishes and bottles can be emptied into the closet.

The inside surface of the slop closet is smooth and is assembled for a proper flushing of the waste. Water flows evenly to the slop closet from the flushing ring under the edge of the pouring hole. Waste is flushed using a manual flushing valve. The closet is also manufactured with a foot operated nozzle for easy rinsing of the containers.

The pouring area of 3075/V slop closet is angled for easier emptying of the containers and improving ergonomics.



### Technical information

Models	3075 Slop closet with rinsing nozzle 3075/V Slop closet with rinsing nozzle, angled
Material	Stainless steel AISI 304
Measurements (width x depth x height)	3075 550 x 600 x 1150 mm (working height 800 mm) 3075/V 550 x 600 x 1150 mm (work height 700 mm)
Accessories included	Hinged lid (blind cover) Foot operated nozzle Plastic trap
Accessories optional	3075 hinged grid, hinged lid with pouring opening 3075V hinged lid with pouring opening
Connections	Cold water connection DN28 (pressure 4,0–8,0 bar) Drain connection DN110
Flush valve	Manual, vacuum breaker included
Flushing time	Default setting 13 l / flushing time 17 s. Adjustable 7,5 - 30 l / flushing time.
Installation	Furniture levellers, wall mounting with screws, water and sewer connections
Manufacturer	KAVIKA OY, Tempo 4, FI-04430 Järvenpää, Finland tel. +358 9 8362 0066, kavika@kavika.fi, www.kavika.fi