

junior_&_senior_hand_dryers ↓

junior hand dryers ↓

Cover: ABS, 1/8" (3 mm) thick
White finish
Size: 11-3/4" x 9-7/8" x 5-1/4"
(300 x 252 x 133 mm)
Weight: 6.6 Lbs. (3 Kg)

Code M88A
Sensor operated



Code M88
Push-button operated
Timer 45"



senior hand dryers ↓

Cover: Aluminium, 1/8" (3 mm) thick
Sensor operated
Size: 11-3/4" x 10" x 5-1/4" (301 x 254 x 134 mm)
Weight: 8.27 Lbs. (3.75 Kg)

Code M89A
White epoxy coated
Code M89AC
Chromed, bright finish
Code M89ACS
Chromed, satin finish



UL/CE technical characteristics	junior	senior
voltage	110 - 120 V / 220 - 240 V	110 - 120 V / 220 - 240 V
frequency	50/60 Hz / 50/60 Hz	50/60 Hz / 50/60 Hz
consumption	11 A / 7 A	11 A / 7 A
motor	1/7 HP / 140 W	1/7 HP / 140 W
rpm	3.300 / 2.800	3.300 / 2.800
heating element	1.200 W / 1.510 W	1.200 W / 1.510 W
effective airflow	111 CFM / 160 m³/h	111 CFM / 160 m³/h
free airflow	139 CFM / 200 m³/h	139 CFM / 200 m³/h
noise level at 2 m	60 dB / 60 dB	60 dB / 60 dB
air speed	3.872 LFM / 60 Km/h	3.872 LFM / 60 Km/h
temperature (at 4" distance / 70 °F)	123.8 °F / 51 °C	123.8 °F / 51 °C
nominal power	1.300 W / 1.650 W	1.300 W / 1.650 W
insulation	Grounding required / class II	Grounding required / class II
drying time	45" / 45"	43" / 43"
splash proof	IP21 - IP23	IP23

junior
inches (mm)

11-3/4" (300)

9-7/8" (252)

5-1/4" (133)

senior
inches (mm)

11-3/4" (301)

10" (254)

5-1/4" (134)