Ceramic Urinal with the Radar Flushing Unit SLP 82RS






SLP 82 - WCA - Sanindusa

Characteristics



- economy flushing by 1 liter of water
- easy installation by the help of paper drill template
- whole flushing unit is placed behind the urinal
- system reacts only on the direct use of the urinal (it analyses changes, which are proceeded inside of the urinal, when a liquid is flowing through)
- adjustable flushing time 0,5 15,5 s
- parameters adjustment by remote control SLD 04 without the necessity to dismantle the urinal from the wall (acoustic setting indication)
- automatic flushing after each 6 hours non-use
- possibility to regulate a water flow by the angle valve
- radar flushing unit recharges a water to the siphon after each flushing

Installation drawing



- 1 waste outlet Ø 50 mm
- 2 5 x holes for fitting
- 3 water inlet G 1/2"
- 4 power supply 24 V DC or 230 V AC
- 6 2 x holes for wall plugs Ø 6 mm (SLP 82RZ)
- 7 power supply (SLP 82RZ)

Technical Specification

Operating voltage

■ SLP 82RS 24 V DC ■ SLP 82RZ 230 V AC/50 Hz

Power input

Water outlet

• operating by 24 V DC 8 W

Recommended flow pressure 0,1 - 0,6 MPa
Rate of flow 18 l/min (inf. data)
Water inlet male thread G 1/2"

inlet fitting

	Dimensions (mm)	Α	В	С	D	Е	F	G	Н	ı	J	К	L	М
	SLP 82 - WCA	500	270	74	150	110	35	90	298	130	225	166	117	48



SLA 11C

SLA 11B

Supply Specification

SLP 82RS

SLA 11C -

Supply No. 01820 ceramic urinal with the radar flushing unit, electromagnetic valve, connecting hoses,

SLP 82RZ - Supply No. 01822 angle valve, inlet fitting, siphon, paper drill template, mounting set, power supply (SLP 99RZ)

Recomended Accessories

Supply No. 06113

SLZ 01Y -**Supply No. 05012** power supply 24 V DC for operating of max. 5 pcs. of flushing units **SLZ 01Z Supply No. 05011** power supply 24 V DC for operating of max. 9 pcs. of flushing units **SLZ 04Y** power supply 24 V DC on DIN rail, for operating of max. 5 pcs. of flushing units **Supply No. 05042** power supply 24 V DC on DIN rail, for operating of max. 9 pcs. of flushing units **SLZ 04Z** Supply No. 05041 **Supply No. 10049** power supply 24 V DC on DIN rail, for operating of max. 15 pcs. of flushing units SLZ 04X -**SLZ 06 Supply No. 05060** power supply 24 V DC for operating of max. 1 pc. of flushing unit **SLD 04 Supply No. 07040** remote control for an adjustment of parameters **SLA 11 Supply No. 06110** deodorising urinal screen - orange colour, mango scent SLA 11A -**Supply No. 06111** deodorising urinal screen - red colour, kiwi and grapefruit scent **SLA 11B Supply No. 06112** deodorising urinal screen - transparent colour, honeysuckle scent

deodorising urinal screen - blue colour, cotton bloom scent